

ORDERING INFORMATION

WARRIOR™ 400i CC/CV , 380-415V 0465 350 886
Supplied with 3m mains cable

Choose one of the following:

Robust Feed PRO- OS, Water Euro 0445 800 883
WARRIOR™ Feed 304w, water 0465 250 881
Mobile Feed AVS 0558 102 222

WARRIOR™ 400i CC/CV PLANT WITH WARRIOR FEED 304 W1009650

Warrior 400i Power Source

Includes: Warrior Feed 304w (fitted with 0.9/1.2mm V Groove feed rolls, interconnection cable 10m, work lead & clamp 5m, Tweco 4, 4.5m Euro MIG Torch, Argon Regulator, Gas Fitting 5/8"-18UNF, Trolley & operation Manual.

WARRIOR™ 400i CC/CV PLANT WITH ROBUST FEED PRO-OS W1009750

Warrior 400i Power Source

Includes: Robust Feed Pro,w (fitted with 0.9/1.2mm V Groove feed rolls, interconnection cable 10m, intercon strain relief, work lead & clamp 5m, Tweco 4, 4.5m Euro MIG Torch, Argon Regulator, Gas Fitting 5/8"-18UNF, Trolley & operation Manual.

ORDERING INFORMATION, CONNECTION CABLES FOR WARRIOR FEED

Select required size and length:

Air cooled 70 mm²

Connection cable 2m 0459 836 880
Connection cable 5m 0459 836 881
Connection cable 10m 0459 836 882
Connection cable 15m 0459 836 883
Connection cable 25m 0459 836 884
Connection cable 35m 0459 836 885

Water cooled 70 mm²

Connection cable 2m 0459 836 890
Connection cable 5m 0459 836 891
Connection cable 10m 0459 836 892
Connection cable 15m 0459 836 893
Connection cable 25m 0459 836 894
Connection cable 35m 0459 836 895

TECHNICAL DATA, WARRIOR™ FEED 304

Power supply, VAC	42
Wire spool capacity, kg	18
Max. spool diameter, mm	300
Wire feed speed, m/min	1.5 - 25.0
Dimension incl. bobbin cover (l x w x h mm)	675 x 264 x 418
Weight incl. bobbin cover, kg	14.5
Wire dimensions:	
Steel	0.6-1.6
Stainless steel	0.6-1.6
Aluminium	0.8-1.6
Cored wire	0.9-1.6
Enclosure class	IP23

TECHNICAL DATA, COOL 2 COOLING UNIT

Power supply, from power source	40V, 50/60Hz
Coolant flow capacity, l/min	1.8
Cooling power, kW	1.0
Max pressure, bar	4.6
Max pressure height to torch, m	8.5
Weight / incl. coolant, kg	15 / 19
Dimensions incl. filler tube l x w x h mm	680 x 325 x 230
Enclosure class	IP23

Cool 2 cooling unit is rated 500 A at 60% duty cycle at 25°C ambient temperature.

ORDERING INFORMATION, TORCHES

Select required size and length:

PSF 515, 3.0m Euro 0700 025 050
PSF 415, 3.0m Euro 0700 025 040
PSF 415, 4.0m Euro 0700 025 041
PSF 420w, 3.0m Euro 0700 025 060
PSF 420w, 4.0m Euro 0700 025 061
PSF 520w, 4.0m Euro 0700 025 071
Tweco 4, 3.6m Euro OTWX412/3545
Tweco 4, 4.5m Euro OTWX415/3545
Tweco Supra XT, 4.0m Euro SE400X4M16

ORDERING INFORMATION, OPTIONS

Trolley 0465 510 880

Remote units


M1 for MIG 8pin; requires cable & Wirefeeder outlet kit 0459 491 895
Remote outlet kit 23pin - Wirefeeder 0465 451 880
Remote cable - 5m; 8pin to 23pin suits M1 remote 0459 553 880
AT1 for MMAW/TIG 8pin; requires cable & power source outlet kit 0459 491 896
AT1 CoarseFine for MMAW/TIG 8pin; requires cable & power source outlet kit 0459 491 897
Remote outlet kit - power source 0465 424 880
Remote cable - 5m; 8pin to 12pin suits AT1 remote 0459 552 880
Remote cable - 10m; 8pin to 12pin suits AT1 remote 0459 552 881
Remote cable - 25m; 8pin to 12pin suits AT1 remote 0459 552 883

Cool 2, water cooler 0465 427 880

Wheel Kit, power source 0465 416 880

Wheel kit, WARRIOR™ feeder 0458 707 880

These welding power sources comply with the requirements of IEC/EN 60974-1 as well as IEC/EN 60974-2 and EN 60974-10

The symbol  indicates that the welding power source may be used in areas with an increased electrical hazard, i.e. areas where the electrical hazard is increased due to damp and/or the proximity to earthed metal objects.

TECHNICAL DATA WARRIOR™ 400i CC/CV

Mains Supply, VAC, 3 ph 50/60Hz	380-400-415, +/-10%
Mains cable, Ø mm²	4 x 6
Fuse, Motor Start Type or Circuit Breaker Type C, A	20
Maximum load at:	
100% duty cycle A/V, 3ph	300/32
60% duty cycle A/V, 3ph	400/36
Setting range A	
MIG/FCAW	16-400
Stick (MMAW)	16-400
TIG	5-400
Open circuit voltage, V	56
Open circuit voltage (VRD ON), V	<35
Idle Power, W	120
Efficiency at max. current %	88
Power factor at max current	0.92
Enclosure class	IP23
Dimensions (l x w x h mm)	712 x 325 x 470
with cooling unit (l x w x h mm)	712 x 325 x 700
Weight, kg	52
With cooling unit excl coolant, kg	67
Operating Temperature, °C	-10 to +40
Application class	S



Tel: 1300 654 674
Email: enquiries@cigweld.com.au
CIGWELD.COM.AU | ESAB.COM





WARRIOR™ 400i CC/CV

Robust inverter welding packages



MIG

STICK

TIG

GOUGING

WARRIOR™ 400i CC/CV POWER SOURCE



FEATURES

BENEFITS

Multi-Process

Includes MIG, Flux-Cored, Stick with Standard Compliant VRD, Live TIG Start and Arc Gouging gives you the flexibility at work:

- Flux-Cored and Solid wire, 0.8 -1.6 mm.
- Carbon Arc Gouging up to 8.0mm (5/16in.).
- 6010 (cellulose) capability.

High Duty cycle

For long runs and various applications giving high productivity.

Durable and rugged

IP23 rating for outdoor and indoor use in rough environment.

Easy to use

Simple and clear user interface for everyone to get started quickly.

Robust and ergonomic handles

Also for mechanical lifting.

Sun friendly display

Easy to read outdoor.

Inverter technology

Smaller, lighter and less energy cost, gives you value for money.

Generator compatible

For flexible use in different job sites.

Automatic Hot Start/Variable Arc Control

To support your different demands.

Wide input voltage range

342V to 456V to accommodate variation in the power grid or generators.

QUALITY AND ENVIRONMENT

APPLICATIONS

IP23 rated - Withstands rain with the fan on.

Air tunnel design - Clean and dirty side in the machine to ensure long-term reliability.

Autofan - Reduces energy consumption and dirt intake.

3 years warranty.

- Fabrication
- Construction
- Pipe Line
- Mobile Machinery
- Outstanding Gouging Capability
- Ship Building
- Energy Generation
- Repair & Maintenance
- Rental

WARRIOR™ OPTIONS

WARRIOR™ FEED 304



Part No.: 0465 250 881

The new user friendly and robust feeder.

- **Rugged design**
– Handle, connectors for tough use.
- **4 roll drive with tacho feedback**
– For superior wire feeding.
- **Sun-friendly display**
– Easy to read outdoor.
- **Bobbin cover**
– Included standard feature for protection.
- **Voltage Pre-set**
– Support the setting of welding parameters.

ROBUST FEED PRO-OS



Part No.: 0445 800 883

The most durable and reliable combination for heavyduty MIG/MAG welding with Stick (MMA), TIG (GTAW), and gouging capabilities.

- Ergonomic, robust and enclosed design
- Equipped with a new precision wire drive system with enough power to handle up to 2.0 mm solid wire and 2.4 mm cored wire

COOLING UNIT - COOL 2



Part No.: 0465 427 880 NOTE: Part No relates to cool unit ONLY

Trolley/Wheel kits

Trolley
Wheel kit power source
Wheel kit feeder

* For more options and ordering information, please see last page.

MOBILE FEED 301AVS



Part No.: 0558 102 222

Portable, durable wire feeder with the most advanced features to meet today's welding requirements.

- Quick-change, four-roll drive reduces downtime providing consistent feeding results; rolls are easily changed without the need for tools
- The sun-friendly display is easy to read outdoors and from a wide range of angles

WARRIOR™ MAIN CONTROLS



WARRIOR™ 400i CC/CV



1. Power On/Off
2. Wire feeder control connector
3. Resettable Circuit Breaker
4. Output Power Connector (+)

5. Output Power Connector (-)
6. Over Temperature indicator
7. VRD indicator in Stick mode
8. Digital Volt/Amp Meter

9. Output Voltage / Current Control
10. Stick electrode type Selector
11. Inductance/Arc Force Control
12. Welding Process Selector