

Maxstar[®] 400

Part No: MR907716002

Exceptionally Smooth & Precise Arc.



| APPLICATIONS | PROCESSES |
|-----------------------------|------------------------|
| Precision Metal Fabrication | TIG (GTAW) |
| Tube Mills | Pulsed TIG (GTAW-P) |
| Pipe and Tube Fabrication | Stick (MMAW) |
| Tool and Die | Air Carbon Arc (CAC-A) |
| Exotic Material Fabrication | |
| Pressure Vessel Fabrication | |

AUTO-POSTFLOW

- > Calculates the length of postflow time based on the Amperage setting.
- > This eliminates the need to independently set the postflow time for different Amperages.
- > This feature preserves your tungsten and prevents porosity.

LIFT-ARC™ STARTING

Provides DC arc initiation without the use of high frequency.

METER CALIBRATION

Allows meters to be calibrated for certification.

Maxstar[®] 400

Part No: MR907716002



DC STICK FEATURES

DIG CONTROL

Allows the arc characteristics to be changed for specific applications and electrodes. Lower the DIG setting for smooth running electrodes like E7018 and increase the DIG setting for stiffer, more penetrating electrodes like E6010.

HOT START[™] ADAPTIVE CONTROL

Provides positive arc starts without sticking.

DC TIG FEATURES

EXCEPTIONALLY SMOOTH AND PRECISE ARC

For welding exotic materials.

DC PULSE

Pulsing can increase puddle agitation, arc stability and travel speeds while reducing heat input and distortion.

FAN-ON-DEMAND[™]

Power source cooling system operates only when needed - reducing noise, energy use and the amount of contaminants pulled through the machine.

COOLER-ON-DEMAND[™]

Operates the auxiliary cooling system only when needed, reducing noise, energy use, and airborne contaminants pulled through the cooler.

PROGRAM MEMORY

Features 9 independent program memories that maintain/save your parameters.

COOLER POWER SUPPLY (CPS)

An integrated 120-volt dedicated-use receptacle for the Coolmate[™] 3.5.

BLUE LIGHTNING[™]

High-frequency arc starter for non-contact arc initiation. Provides more consistent arc starts and greater reliability.

WIND TUNNEL TECHNOLOGY[™]

Protects internal electrical components from airborne contaminants, extending the product life.

3 YEAR WARRANTY

For details, refer to Miller's True Blue warranty statement.

| AMP RANGE | PHASE | RATED OUTPUT | AMPS INPUT AT RATED OUTPUT, 50/60 HZ | | | MAX. OPEN-CIRCUIT VOLT. | DIM. (MM) | WEIGHT |
|-----------|-------|----------------------------------|--------------------------------------|-----|------|--|--|------------------------------|
| | | | 400V | KVA | KW | | | |
| 3 - 400A | 3 | 250 A at 30 V 100% Duty Cycle | 14 | 9.4 | 9.1 | 75 VDC (10-15 VDC-VRD*) *Indicates sense-voltage for Lift-Arc [™] TIG and VRD stick. | H: 629 mm W: 349 mm D: 559 mm with TIGRunner H: 1095 mm W: 587 mm D: 1111 mm | 61kg with TIGRunner 114kg |
| | | 300 A at 32 V 60% Duty Cycle | 17 | 12 | 11.6 | | | |



Maxstar[®] 400

Part No: MR907716002



ORDERING INFORMATION - AVAILABLE BASE PACKAGES

WATER-COOLED PACKAGE (TIG ONLY)

POWER SOURCE

MR907716002 Maxstar 400

REQUIRED ACCESSORIES

MR300245 Coolmate 3.5

KIT0007 Water-cooled TIG kit - includes 8m TIG torch, argon gas regulator, 5m work lead with earth clamp, 500A G type & dinse plug, 5m gas hose

MR043810 Coolant

WGAK3 Torch accessory kit

OPTIONAL ACCESSORIES

MR195377 Water-cooled torch dinse adaptor (Note: Not required if ordering TIG kit KIT0007)

HA801AR Argon regulator & flow gauge (Note: Not required if ordering TIG kit KIT0007)

MR187208 RMS-14 momentary push button 8m (Note: Not required if ordering TIG kit KIT0007)

MR151086 RCC-14 TIG remote fingertip current control (Note: Not required if ordering TIG kit KIT0007)

MR242211020 RHC-14 remote hand current control

MR300430 Wireless hand control & 14 pin receiver

MR300429 Wireless foot control & 14 pin receiver

MR300244 Runner cart



welding.com.au 1300 300 884